

RM170+™



PICK-UP AND DELIVERY ALL-POSITION

The RM170+™ is a pick-up and delivery all-position tire offering improved handling, wear, and an increased speed rating (225/70R19.5 F&G, 245/70R19.5 G) over that of its predecessor, the RM170™. The solid shoulder and high tensile strength belt construction combine to provide the retreadability and treadwear that local P&D haulers require.

N (87MPH) SPEED RATING

225/70R19.5 and 245/70R19.5 LR G sizes offer N speed rating.

V-SHAPED TREAD GROOVES

Groove shape works to reduce stone retention.

WIDE TREAD AND OPTIMIZED FOOTPRINT

Delivers long, even treadwear.

STONE EJECTORS

Stone ejectors in the tread grooves protect the casing from stone penetrations.

Material #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REV/s miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000039342	225/70R19.5 F/12 125/123N 87 mph 140 km/h	(6.75) 6.00-6.00	95 660	3,640 1,650	3,415 1,550	32.05 814	9.00 228	14.92 379	10.0 254	647 402	15.0 11.9	28 7.11	7.6 193	62 28.0	029142957232
90000039343	225/70R19.5 G/14 128/126N 87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.05 814	9.00 228	14.92 379	10.0 254	647 402	15.0 11.9	28 7.11	7.6 193	62 28.0	029142957249
90000039345	245/70R19.5 G/14 133/131N 87 mph 140 km/h	(7.50) 6.75-7.50	110 760	4,540 2,060	4,300 1,950	33.11 841	9.90 251	15.35 390	11.0 279	626 389	16.0 12.7	26 660	8.4 213	71 32.2	029142957263
90000039344	245/70R19.5 H/16 136/134M 81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.11 841	9.90 251	15.35 390	11.0 279	626 389	16.0 12.7	26 660	8.4 213	71 32.2	029142957256
90000039346	265/70R19.5 G/14 137/134L 75 mph 120 km/h	(7.50) 7.50-8.25	110 760	5,070 2,300	4,675 2,120	34.37 873	10.30 261	15.87 403	11.6 295	603 375	17.5 13.8	30 762	8.6 219	81 37.0	029142957270
90000039350	285/70R19.5 H/16 146/144L 75 mph 120 km/h	(8.25) 7.50-9.00	125 850	6,610 3,000	6,170 2,800	35.20 894	10.90 277	16.22 412	12.5 318	589 366	17.5 13.8	30 762	9.0 229	88 40.0	029142957300
90000039347	10R22.5 G/14 141/139L 75 mph 120 km/h	(7.50) 6.75-8.25	115 790	5,675 2,575	5,355 2,430	40.31 1024	10.10 257	18.82 478	11.4 290	514 320	18.0 14.5	24 610	7.9 200	101 45.9	029142957287

This new line will replace the RM170 in May 2020.

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.