

RM230 HH



ON/OFF-ROAD ALL-POSITION

The RM230HH is an on/off-road all-position tire designed to handle heavy hauling. The robust tread pattern, tread compounding and high tensile strength four-belt package combine to provide the retreadability, treadwear, and cut and chip resistance that your fleets require.

CUT AND CHIP RESISTANT TREAD COMPOUND

The cut and chip resistant tread compounding is specifically designed to perform in mixed service applications.

STONE PROTECTOR LEDGE

Stone protector ledges on all grooves resist stone penetrations.

CURB BAR WITH SIDEWALL DEPTH INDICATOR

Protects the sidewall from scuffing damage and indicates when a tire should be rotated to preserve the casing for retreading.

DEEP TREAD DEPTH

22.5/32" tread depth provides extended tread life in on/off-road applications.

Material #	Item #	Tire Size, Load Range / Ply Rating, Service Description & Max Speed				(Measured) Approved Rim Widths	Max. Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcng. inch mm	REV's miles kilo	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg	UPC
90000024676	n/a	275/70R22.5	J/18	148/145K	68 mph 110 km/h	(8.25) 7.5-8.25	130 900	6,940 3,150	6,395 2,900	37.87 962	11.10 281	17.60 447	11.9 303	547 340	22.0 660	26 220	8.64 215	115	029142837602
90000007239	93336	11R22.5	H/16	146/143K	68 mph 110 km/h	(8.25) 7.5-8.25	120 830	6,610 3,000	6,005 2,725	41.65 1,058	11.10 283	19.41 493	12.5 318	498 309	22.5 660	26 229	9.02 229	123	029142663843
90000007238	93322	12R22.5	H/16	150/147K	68 mph 110 km/h	(9.0) 8.25-9.0	120 830	7,390 3,350	6,780 3,075	42.91 1,090	12.00 304	19.92 506	13.5 343	483 300	22.5 660	26 244	9.61 244	142	029142692850
90000007243	93356	11R24.5	H/16	149/146K	68 mph 110 km/h	(8.25) 7.5-8.25	120 830	7,160 3,250	6,610 3,000	43.66 1,109	11.10 281	20.39 518	12.5 318	475 295	22.5 660	26 229	9.02 229	132	029142663850
90000007242	93324	12R24.5	H/16	152/149K	68 mph 110 km/h	(9.0) 8.25-9.0	120 830	7,830 3,550	7,160 3,250	45.00 1,143	12.10 307	20.94 532	13.5 343	461 286	22.5 660	26 244	9.61 244	152	029142692867

Refer to the Load and Inflation Table for approved tire load limits at various cold inflation pressures.

Exceeding posted speed limits is unlawful and is not recommended by Cooper Tire.

Please refer to the Commercial Truck Tire and Vehicle Safety reference pages for proper care and service of truck and bus tires.

Cooper Tire reserves the right to change and improve construction, materials or specifications without notice or obligation.



Visit cooperworld.net for up-to-date spec information.