

COMMERCIAL TRUCK TIRES

# ROADMASTER PRODUCT BROCHURE



**ROADMASTER<sup>®</sup> TIRES**

2023

## LONG HAUL

### STEER



RM832+<sup>EM</sup><sup>™</sup>  
page 2

### DRIVE



RM852<sup>EM</sup><sup>™</sup>  
page 3

RM275<sup>™</sup>  
page 4

### TRAILER



RM872<sup>EM</sup><sup>™</sup>  
page 5

RM120<sup>™</sup>  
page 6

## REGIONAL

### STEER & ALL-POSITION



RM234<sup>EM</sup><sup>™</sup>  
page 7

RM830<sup>EM</sup><sup>™</sup>  
page 8

RM185<sup>™</sup>  
page 9

### DRIVE



RM254<sup>™</sup>  
page 10

RM258 WD<sup>™</sup>  
page 11

### TRAILER



RM272<sup>™</sup>  
page 12

RM170<sup>™</sup>  
page 13

## MIXED SERVICE

### STEER & ALL-POSITION



RM230 HH<sup>™</sup>  
page 14

RM230 HH+<sup>™</sup>  
page 15

RM230 WH<sup>™</sup>  
page 16

RM230 WB<sup>™</sup>  
page 17

RM332 WB<sup>™</sup>  
page 18

### DRIVE



RM300 HH<sup>™</sup>  
page 19

RM351 HD<sup>™</sup>  
page 20

## URBAN

### STEER/ALL POSITION



RM170+<sup>™</sup>  
page 21

### DRIVE



RM257<sup>™</sup>  
page 22



**ROADMASTER TIRES**

Visit us at:  
[www.roadmastertires.com](http://www.roadmastertires.com)

Table of Contents	Page
Long Haul Tires .....	2-6
Regional Tires.....	7-13
Mixed Service Tires.....	14-20
Urban .....	21-22
Tire Selection Guide .....	23
RMT Load and Inflation Table .....	24
Warranty .....	25



## Roadmaster Commercial Truck Tire Size Matrix

Rim Diameter	Tire Size	STEER / ALL-POSITION										DRIVE				TRAILER							
		Long Haul	Regional			P&D	On / Off-Road					Long Haul	Regional	P&D	On / Off-Road	Long Haul	Regional						
		RM832+™	RM234™	RM185™	RM830™	RM170+™	RM230 HH™	RM230 WH™	RM230 HH+™	RM230 WB™	RM332 WB™	RM852™	RM275™	RM254™	RM258 WD™	RM257™	RM300 HH™	RM651 HD™	RM872™	RM120™	RM272™	RM170™	
17.5	245/70R17.5																					J	
	215/75R17.5																					H	H
	235/75R17.5																						J
19.5	225/70R19.5						F / G								F / G								
	245/70R19.5						G / H								G / H								
	265/70R19.5						G																
22.5	385/65R22.5									L	L												
	425/65R22.5									L	L												
	255/70R22.5														H							H	
	275/70R22.5						J															J	
	295/75R22.5	G / H	G / H	G							G	G	G						G	G		G / H	
	315/80R22.5				L				L	L													
10R22.5	10R22.5					G																	
	11R22.5	G / H	G / H	G / H			H						G / H	G / H	G / H	H		H	H	G		G / H	
	12R22.5						H																
24.5	285/75R24.5	H	G	G									G	G	G					G			
	11R24.5	G / H	G / H	G / H			H						G / H	G / H	G / H	H		H	H	G		H	
	12R24.5						H																

# LONG HAUL | STEER

SmartWay®  
VERIFIED



## RM832+ EM™

The RM832+ EM™ is Roadmaster's newest SmartWay verified long haul steer tire for long miles to removal.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

### 2ND-GENERATION ENERGY MAX FUEL-EFFICIENT COMPOUND

The tire's tread design coupled with next generation rubber compounding helps provide low rolling resistance, earning SmartWay verification.

### DECOUPLING RIB DESIGN

The patent-pending shoulder-decoupling rib design helps provide even shoulder wear and durability.

### STONE PROTECTOR LEDGES

Ledges in center grooves help resist stone penetration, helping to preserve the casing for retread.

**Competitive Replacements:** Uniroyal LS2, Falken RI130 Ecorun, Kumho KLS12e / KLS02e, Double Coin FR610

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246455	173-008-018	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.20 1,021	11.3 287	18.78 477	12.9 327	516 320	18.0 14.4	24 610	9.5 241	116 52.6
246456	173-023-018	295/75R22.5	H/16	149/146L	75 mph 120 km/h	(8.25) 8.25-9.00	125 850	7,160 3,250	6,610 3,000	40.20 1,021	11.3 287	18.78 477	12.9 327	516 320	18.0 14.4	24 610	9.5 241	116 52.6
246327	173-004-018	11R22.5	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.69 1,059	11.1 281	19.41 493	12.5 318	497 309	18.0 14.4	24 610	9.1 230	119 54.1
246454	173-032-018	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	41.73 1,060	11.1 283	19.41 493	12.5 318	497 309	18.0 14.4	24 610	9.1 230	119 54.1
246461	173-035-018	285/75R24.5	H/16	147/144L	75 mph 120 km/h	(8.25) 7.50-9.00	120 830	6,780 3,075	6,175 2,800	41.38 1,051	10.9 278	19.41 493	12.5 318	501 311	18.0 14.4	26 660	9.4 238	120 54.5
246459	173-033-018	11R24.5	G/14	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	43.70 1,110	11.1 281	20.39 518	12.5 318	474 295	18.0 14.4	24 610	9.1 232	128 58.2
246460	173-034-018	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	43.74 1,111	11.0 280	20.43 519	12.5 318	474 295	18.0 14.4	24 610	9.1 232	128 58.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# LONG HAUL | DRIVE

SmartWay®  
VERIFIED



## RM852 EM™

The RM852 EM is a long haul drive tire that is SmartWay verified. The tread is designed to help promote even wear and contains Energy Max compounds for long miles to removal.

### EM ENERGY MAX FUEL-EFFICIENT COMPOUND

The tire's tread design and rubber compounding helps provide low tire rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

### 3D MICRO SIPING

The 3D micro-gauge siping, along with the solid shoulder design, helps deliver traction in diverse weather conditions.

### SOLID SHOULDER RIBS

Solid shoulder ribs help provide even wear in long haul applications, while the lugs provide traction in wet and snowy conditions.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

**M+S Rated**

**Competitive Replacements:** Uniroyal LD2, Falken BI830, Kumho KLD02e, Double Coin FD405

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246443	173-008-019	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.94 1,040	11.4 289	19.09 485	12.9 327	506 315	30.0 23.7	28 711	9.6 245	130 58.9
246275	173-004-019	11R22.5	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	42.13 1,070	11.5 292	19.61 498	12.5 318	492 306	30.0 23.7	26 660	9.8 248	134 60.8
246439	173-003-019	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	42.17 1,071	11.5 293	19.61 498	12.5 318	492 306	30.0 23.7	26 660	9.8 248	136 61.6
246442	173-007-019	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	42.20 1,072	10.7 273	19.76 502	12.5 318	491 305	30.0 23.7	28 711	9.5 241	135 61.4
246441	173-006-019	11R24.5	G/14	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	44.13 1,121	11.3 287	20.59 523	12.5 318	470 292	30.0 23.7	26 660	9.8 248	143 65.1
246440	173-005-019	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	44.13 1,121	11.4 289	20.59 523	12.5 318	470 292	30.0 23.7	26 660	9.8 248	145 66.0

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# LONG HAUL | DRIVE



## RM275™

The RM275™ is a solid-shoulder long haul drive tire for long miles to removal.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

### SOLID-SHOULDER RIBS

Solid shoulder ribs help provide even wear in long haul applications, while the lugs help provide traction in wet and snowy conditions.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

**Competitive Replacements:** Uniroyal LD2, Falken BI837, Kumho KLD11e/KRD01, Double Coin RLB400

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246331	173-008-012	295/75R22.5	G/14	144/141L	75 mph 120 km/h	(8.25) 8.25-9.00	110 760	6,175 2,800	5,675 2,575	40.63 1,032	11.1 281	18.94 481	12.9 327	510 317	26.5 21.2	26 660	8.7 222	114 51.8
246210	173-004-011	11R22.5	G/14	144/142L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,175 2,800	5,840 2,650	41.93 1,065	11.0 279	19.49 495	12.5 318	494 307	26.5 21.2	22 559	8.9 225	123 56.0
246424	173-003-011	11R22.5	H/16	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	6,610 3,000	6,005 2,725	42.05 1,068	11.0 279	19.57 497	12.5 318	493 306	26.5 21.2	22 559	8.9 225	125 56.8
246427	173-015-011	285/75R24.5	G/14	144/141L	75 mph 120 km/h	(8.25) 7.50-9.00	110 760	6,175 2,800	5,675 2,575	41.85 1,063	10.7 273	19.61 498	12.5 318	495 308	26.5 21.2	22 559	8.9 225	118 53.5
246426	173-006-011	11R24.5	G/14	146/143L	75 mph 120 km/h	(8.25) 7.50-8.25	105 720	6,610 3,000	6,005 2,725	44.02 1,118	10.8 275	20.55 522	12.5 318	471 293	26.5 21.2	24 610	8.6 219	132 59.9
246425	173-005-011	11R24.5	H/16	149/146L	75 mph 120 km/h	(8.25) 7.50-8.25	120 830	7,160 3,250	6,610 3,000	44.06 1,119	10.8 274	20.55 522	12.5 318	471 292	26.5 21.2	24 610	8.6 219	134 60.8

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# LONG HAUL | TRAILER

SmartWay®  
VERIFIED



## RM872<sup>EM</sup>

The RM872<sup>EM</sup> is a fuel-efficient SmartWay verified long haul trailer tire for long miles to removal.

### **EM ENERGY MAX FUEL-EFFICIENT COMPOUND**

The tire's tread design and rubber compounding help provide low tire rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

### **WIDE OUTSIDE SHOULDER RIBS**

The wide shoulder and center ribs help resist scrubbing from high side forces, which helps promote long, even wear for long haul applications.

### **MICRO SIPES**

Micro sipes help provide enhanced traction in wet road conditions and help resist abnormal or "river wear."

### **STONE PROTECTORS**

Stone protectors in the bottom of the tread grooves help protect the casing from stone penetration and help resist stone retention.

**Competitive Replacements:** Uniroyal LT2/LS2, Falken RI-119 ECORUN, Kumho KLT12e, Double Coin FT105/FT115

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246333	173-008-020	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	39.72	11.3	18.58	12.9	522	12.0	26	8.7	102
					120 km/h		760	2,800	2,575	1,009	287	472	327	324	9.5	660	222	46.3
246416	173-004-020	11R22.5	G/14	144/142L	75 mph	(8.25) 7.50-8.25	105	6,175	5,840	40.94	11.1	19.09	12.5	506	12.0	24	8.5	106
					120 km/h		720	2,800	2,650	1,040	281	485	318	315	9.5	610	216	48.1
246418	173-015-020	285/75R24.5	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	40.98	10.8	19.25	12.5	506	12.0	26	8.7	109
					120 km/h		760	2,800	2,575	1,041	274	489	318	314	9.5	660	222	49.4
246417	173-006-020	11R24.5	G/14	146/143L	75 mph	(8.25) 7.50-8.25	105	6,610	6,005	42.95	11.2	20.08	12.5	483	12.0	24	8.5	114
					120 km/h		720	3,000	2,725	1,091	284	510	318	300	9.5	610	216	51.7

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# LONG HAUL | TRAILER



## RM120™

The RM120™ is a long haul trailer tire for even wear and miles to removal.

### MICRO SIPES

Micro sipes help provide enhanced traction in wet road conditions and helps resist abnormal or "river wear."

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

### HIGH TENSILE STRENGTH

### FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**Competitive Replacements:** Kumho KRSS0/KRT03a, Double Coin TR100

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246534	173-043-028	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	39.65	11.1	18.54	12.9	523	12.0	26	8.7	100
					120 km/h		760	2,800	2,575	1,007	281	471	327	325	9.5	660	222	45.4

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



# REGIONAL | STEER & ALL-POSITION

SmartWay®  
VERIFIED



## RM234<sup>EM</sup>™

The RM234<sup>EM</sup>™ is a SmartWay verified regional steer & all-position tire for long miles to removal.

### **EM ENERGY MAX FUEL-EFFICIENT COMPOUND**

The tire's tread design and rubber compounding helps provide low tire rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

### **HIGH-SCRUB TREAD COMPOUND**

Advanced tread compound helps provide improved treadwear and protection against cutting and chipping.

### **STONE PROTECTORS**

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

**Competitive Replacements:** Uniroyal RS2, Falken RI150, Kumho KRS12e / KRS02e, Double Coin RT606+

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246432	173-008-007	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	40.39	11.1	18.86	12.9	513	22.5	30	8.9	113
					120 km/h		760	2,800	2,575	1,026	283	479	327	319	18.0	762	225	51.3
246438	173-023-007	295/75R22.5	H/16	149/146L	75 mph	(8.25) 8.25-9.00	125	7,160	6,610	40.39	11.1	18.86	12.9	513	22.5	30	8.9	115
					120 km/h		850	3,250	3,000	1,026	283	479	327	319	18.0	762	225	52.1
246431	173-004-007	11R22.5	G/14	144/142L	75 mph	(8.25) 7.50-8.25	105	6,175	5,840	41.65	11.3	19.41	12.5	498	22.5	26	8.9	118
					120 km/h		720	2,800	2,650	1,058	286	493	318	309	18.0	660	225	53.6
246344	173-003-007	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.69	11.3	19.41	12.5	497	22.5	26	8.9	122
					120 km/h		830	3,000	2,725	1,059	286	493	318	309	18.0	660	225	55.4
246435	173-007-007	285/75R24.5	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	41.69	10.8	19.57	12.5	497	22.5	30	8.9	118
					120 km/h		760	2,800	2,575	1,059	274	497	318	309	18.0	762	225	53.7
246434	173-006-007	11R24.5	G/14	146/143L	75 mph	(8.25) 7.50-8.25	105	6,610	6,005	43.58	11.1	20.35	12.5	476	22.5	26	8.9	129
					120 km/h		720	3,000	2,725	1,107	281	517	318	296	18.0	660	225	58.4
246433	173-005-007	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.58	11.1	20.35	12.5	476	22.5	26	8.9	129
					120 km/h		830	3,250	3,000	1,107	281	517	318	296	18.0	660	225	58.4

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# REGIONAL | STEER & ALL-POSITION

SmartWay®  
VERIFIED



## RM830<sup>EM</sup>

The RM830<sup>EM</sup> is a regional all-position SmartWay verified tire for long miles to removal.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

### <sup>EM</sup> ENERGY MAX FUEL-EFFICIENT COMPOUND

The tire's tread design and rubber compounding helps provide low rolling resistance and contributes to fuel efficiency, earning SmartWay verification.

### 5-RIB TREAD DESIGN

Chevron-shaped ribs help provide even wear and traction.

### RADIAL SIPING

Radial siping helps enhance traction in wet conditions.

### OPTIMIZED FOOTPRINT

The optimized footprint helps deliver even wear.

**Competitive Replacements:** Falken RI151, Kumho KRS03, Double Coin RR680

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246277	173-024-016	315/80R22.5	L/20	157/154L	75 mph	(9.00) 9.00-9.75	130	9,090	8,270	42.20	12.3	19.61	13.8	491	18.0	26	9.5	130
					120 km/h		900	4,125	3,750	1,072	312	498	351	305	14.5	660	241	59.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# REGIONAL | STEER & ALL-POSITION

SmartWay®  
VERIFIED



## RM185™

The RM185™ is a regional all-position tire that is SmartWay verified for steer axle applications.

### FUEL-EFFICIENT COMPOUND

Tire design and rubber compounding help provide low rolling resistance and contribute to fuel efficiency, earning Smartway verification.

### ALL-POSITION TREAD PATTERN

18/32" tread depth combined with solid shoulder ribs helps with regional haul and and pick-up and delivery service.

### MICRO SIPES

Micro sipes help provide enhanced traction in wet road conditions and resists abnormal or "river wear."

### HIGH TENSILE STRENGTH

### FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**Competitive Replacements:** Uniroyal RS2, Falken RI151, Kumho KRS12e / KRS02e, Double Coin FR605

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246205	173-008-026	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	40.08	11.2	18.74	12.9	517	18.0	26	8.7	107
					120 km/h		760	2,800	2,575	1,018	285	476	327	321	14.4	660	222	48.6
246411	173-004-025	11R22.5	G/14	144/142L	75 mph	(8.25) 7.50-8.25	105	6,175	5,840	41.38	11.2	19.29	12.5	501	18.0	24	8.5	111
					120 km/h		720	2,800	2,650	1,051	284	490	318	311	14.5	610	216	50.7
246204	173-003-025	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.38	11.2	19.29	12.5	501	18.0	24	8.5	113
					120 km/h		830	3,000	2,725	1,051	284	490	318	311	14.5	610	216	51.5
246414	173-007-025	285/75R24.5	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	41.50	10.7	19.49	12.5	500	18.0	26	8.4	114
					120 km/h		760	2,800	2,575	1,054	272	495	318	310	14.5	660	213	51.7
246413	173-006-025	11R24.5	G/14	146/143L	75 mph	(8.25) 7.50-8.25	105	6,610	6,005	43.43	11.0	20.28	12.5	477	18.0	22	8.7	120
					120 km/h		720	3,000	2,725	1,103	279	515	318	297	14.5	559	222	54.4
246412	173-005-025	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.43	11.0	20.28	12.5	477	18.0	22	8.7	122
					120 km/h		830	3,250	3,000	1,103	280	515	318	297	14.5	559	222	55.3

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM254™

The RM254™ is a regional drive tire that helps provide traction and tread wear for frequent stopping and accelerating.

### AGGRESSIVE TRACTION TREAD PATTERN

The aggressive traction tread pattern provides traction and treadwear in various weather conditions.

### ROBUST TIE BARS

Robust tie-bars help to resist cracking, tearing and heel-toe wear.

### STONE PROTECTOR LEDGES

Stone protector ledges on lugs help resist stone penetration.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

The curb bar with sidewall depth indicator helps protect the sidewall from scuffing damage and assists in indicating when a tire should be rotated to preserve the casing for retreading.

### CUT AND CHIP TREAD COMPOUND FOR LOAD RANGE H SIZE

The tread compound used in the load range H sizes is specifically designed to help resist cuts and chips in mixed service applications.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**M+S Rated**

**Competitive Replacements:** Uniroyal RD2, Falken BI850, Kumho KRD23/KRD03, Double Coin RLBI/RLBII

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246350	173-008-008	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	40.79	11.1	19.02	12.9	508	26.0	28	9.0	116
					120 km/h		760	2,800	2,575	1,036	281	483	327	316	20.7	711	229	52.9
246209	173-004-008	11R22.5	G/14	144/142L	75 mph	(8.25) 7.50-8.25	105	6,175	5,840	41.89	11.2	19.49	12.5	495	26.0	26	8.6	119
					120 km/h		720	2,800	2,650	1,064	285	495	318	308	20.7	660	218	54.1
246349	173-003-008	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.97	11.3	19.53	12.5	494	26.0	26	8.6	121
					120 km/h		830	3,000	2,725	1,066	288	496	318	307	20.7	660	218	55.0
246423	173-015-008	285/75R24.5	G/14	144/141L	75 mph	(8.25) 7.50-9.00	110	6,175	5,675	41.89	10.8	19.65	12.5	495	26.0	28	9.0	122
					120 km/h		760	2,800	2,575	1,064	274	499	318	308	20.7	711	229	55.3
246421	173-006-008	11R24.5	G/14	146/143L	75 mph	(8.25) 7.50-8.25	105	6,610	6,005	43.90	11.1	20.51	12.5	472	26.0	26	8.6	127
					120 km/h		720	3,000	2,725	1,115	281	521	318	293	20.7	660	218	57.9
246422	173-005-008	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.94	11.1	20.51	12.5	472	26.0	26	8.6	131
					120 km/h		830	3,250	3,000	1,116	281	521	318	293	20.7	660	218	59.3

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM258 WD™

The RM258 WD™ is an open-shoulder regional drive tire, for performance in various winter conditions.

### 3D SIPING

3D corrugations on the sipes help to lock the tread blocks together to help maintain stability for traction.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

### CHEVRON GROOVES

Biting edges help enhance traction.

### OPTIMIZED SHOULDER DESIGN

Notches in shoulder lugs help provide traction while tie-bars help prevent heel-toe wear.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.



**M+S Rated**

**Competitive Replacements:** Uniroyal RD2/RSD1, Double Coin RSD3

\* Meets Three-Peak Mountain Snowflake (3PMSF) Traction Requirements

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246167	173-036-010	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.97	11.2	19.53	12.5	494	26.0	28	9.8	121
					120 km/h		830	3,000	2,725	1,066	285	496	318	307	20.7	711	248	55.2
246448	173-011-010	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	44.21	11.1	20.63	12.5	469	26.0	28	9.8	135
					120 km/h		830	3,250	3,000	1,123	283	524	318	291	20.7	711	248	61.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# REGIONAL | TRAILER



## RM272™

The RM272™ is an all-position/trailer tire featuring a high-scrub tread compound.

### HIGH-SCRUB TREAD COMPOUND

The tread compound helps to provide improved treadwear and resists cutting and chipping.

### ROUNDED SHOULDER PROFILE

The rounded shoulder design helps minimize the effect of high lateral forces in spread-axle applications.

### STONE PROTECTORS

The stone protectors in the center grooves help protect the casing from stone penetration and help resist stone retention.

### MULTI-PURPOSE SIZE DESIGN

The 255/70R22.5 is designed with 16/32" tread depth which can be used on spread-axle trailers, straight trucks and recreational vehicles.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**Competitive Replacements:** Falken BI850, Kumho KRT03a/KRT12, Double Coin RT500

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
254277	173-001-001	215/75R17.5	H/16	135/133L	75 mph	(6.00) 6.00-6.75	123	4,805	4,540	30.51	8.5	14.29	9.4	680	16.0	18	7.1	60
					120 km/h		850	2,180	2,060	775	216	363	239	422	12.6	457	181	27.1
246473	173-022-001	245/70R17.5	J/18	143/141K	68 mph	(6.75) 6.75-7.50	125	6,005	5,675	31.22	9.5	14.41	10.6	664	14.5	22	8.5	67
					110 km/h		875	2,725	2,575	793	242	366	270	413	11.5	559	216	30.6
246335	173-017-001	255/70R22.5	H/16	140/137L	75 mph	(8.25) 6.75-8.25	120	5,510	5,070	36.69	10.3	17.09	11.6	565	16.0	28	8.3	90
					120 km/h		830	2,500	2,300	932	262	434	295	351	12.6	711	210	40.8
246419	173-018-001	275/70R22.5	J/18	148/145L	75 mph	(8.25) 7.50-8.25	130	6,940	6,395	38.07	11.0	17.68	12.2	545	18.0	28	9.0	105
					120 km/h		900	3,150	2,900	967	279	449	311	338	14.5	711	229	47.9
246437	173-004-001	11R22.5	G/14	144/142L	75 mph	(8.25) 7.50-8.25	105	6,175	5,840	41.22	11.3	19.21	12.5	503	16.0	24	8.9	111
					120 km/h		720	2,800	2,650	1,047	287	488	318	313	12.7	610	225	50.3
246276	173-003-001	11R22.5	H/16	146/143L	75 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.22	11.2	19.21	12.5	503	16.0	24	8.5	113
					120 km/h		830	3,000	2,725	1,047	284	488	318	313	12.7	610	216	51.2
253647	173-008-001	295/75R22.5	G/14	144/141L	75 mph	(8.25) 8.25-9.00	110	6,175	5,675	39.92	11.1	18.66	12.9	519	16.0	28	8.5	106
					120 km/h		760	2,800	2,575	1,014	281	474	327	323	12.7	711	216	48.2
246445	173-023-001	295/75R22.5	H/16	149/146L	75 mph	(8.25) 8.25-9.00	125	7,160	6,610	39.88	11.1	18.62	12.9	520	16.0	28	8.5	108
					120 km/h		850	3,250	3,000	1,013	282	473	327	323	12.7	711	216	49.0
246444	173-005-001	11R24.5	H/16	149/146L	75 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.31	11.1	20.24	12.5	479	16.0	24	8.5	122
					120 km/h		830	3,250	3,000	1,100	282	514	318	297	12.7	610	216	55.4

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM170™

The RM170™ is a regional pick-up and delivery all-position tire and, with the addition of the 17.5" size, can also be used on low-platform trailers.

### WIDE TREAD AND OPTIMIZED FOOTPRINT

The wide tread and optimized footprint help deliver even wear.

### V-SHAPED TREAD GROOVES

The groove shape works to help reduce stone retention.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

### HIGH TENSILE STRENGTH

### FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246203	173-001-023	215/75R17.5	H/16	135/133L	75 mph	(6.00) 6.00-6.75	125	4,805	4,540	30.51	8.4	14.29	9.4	680	15.0	18	7.1	59
					120 km/h		850	2,180	2,060	775	213	363	239	422	12.1	457	181	26.6
246380	173-002-023	235/75R17.5	J/18	143/141J	62 mph	(6.75) 6.75-7.50	125	6,005	5,675	31.46	9.1	14.69	10.3	659	15.0	24	7.5	67
					100 km/h		860	2,725	2,575	799	232	373	262	410	12.1	610	191	30.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM230 HH™

The RM230HH™ is an all-position mixed service tire for heavy hauling in urban environments.

### CUT AND CHIP TREAD COMPOUND

The tread compound helps resist cuts and chips in mixed service applications.

### STONE PROTECTOR LEDGES

Stone protector ledges on all grooves help resist stone penetration and retention.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

The curb bar with sidewall depth indicator helps protect the sidewall from scuffing damage and assists in indicating when a tire should be rotated to preserve the casing for retreading.

### DEEP TREAD DEPTH

The 22.5/32" tread depth helps provide long miles to removal in on/off-road applications.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**Competitive Replacements:** Uniroyal HS2, Falken G1388, Kumho KMA01, Double Coin RR706

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246341	173-021-005	275/70R22.5	J/18	148/145K	68 mph	(8.25) 7.50-8.25	130	6,940	6,395	38.27	11.0	17.76	12.2	542	22.0	26	8.70	115
					110 km/h		900	3,150	2,900	972	279	451	311	337	17.5	660	220	52.1
246346	173-037-005	11R22.5	H/16	146/143K	68 mph	(8.25) 7.50-8.25	120	6,610	6,005	41.61	11.3	19.37	12.5	498	22.5	26	9.0	122
					110 km/h		830	3,000	2,725	1,057	286	492	318	310	18.0	660	229	55.4
246206	173-009-005	12R22.5	H/16	150/147K	68 mph	(9.00) 8.25-9.00	120	7,390	6,780	42.83	12.0	19.88	13.5	484	22.5	26	9.6	140
					110 km/h		830	3,350	3,075	1,088	305	505	343	301	18.0	660	244	63.8
246485	173-011-005	11R24.5	H/16	149/146K	68 mph	(8.25) 7.50-8.25	120	7,160	6,610	43.66	11.0	20.39	12.5	475	22.5	26	9.0	130
					110 km/h		830	3,250	3,000	1,109	279	518	318	295	18.0	660	229	59.3
246347	173-014-005	12R24.5	H/16	152/149K	68 mph	(9.00) 8.25-9.00	120	7,830	7,160	45.00	11.9	20.94	13.5	461	22.5	26	9.6	150
					110 km/h		830	3,550	3,250	1,143	301	532	343	286	18.0	660	244	68.1

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.





## RM230 HH+™

The RM230 HH+™ is a mixed service on/off-road all-position tire designed to handle heavy hauling in high-scrub applications.

### INNOVATIVE TREAD COMPOUND

The tread compound helps with heavy hauling and high-scrub applications.

### DEEP TREAD DEPTH

The 23/32" tread depth helps provide long miles to removal in high-scrub applications.

### STONE PROTECTOR LEDGES

Stone protector ledges on all grooves help resist stone penetration and retention.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

The curb bar with sidewall depth indicator helps protect the sidewall from scuffing damage and assists in indicating when a tire should be rotated to preserve the casing for retreading.

### 10,000-LB. LOAD-CARRYING CAPACITY

A robust tire construction helps provide the load-carrying capacity for high-load steer axles.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**Competitive Replacements:** Uniroyal HS2, Falken GI 388, Kumho KMA01, Double Coin RR706

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246334	173-016-006	315/80R22.5	L/20	160/154J	62 mph	(9.00) 9.00-9.75	130	10,000	8,270	42.80	12.4	19.88	13.8	484	22.5	28	10.0	148
					100 km/h		900	4,540	3,750	1,087	316	505	351	301	18.0	711	254	67.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM230 WH™

The RM230 WH™ is a steer all-position waste haul tire for urban environments.

### ADVANCED TREAD WIDTH AND TREAD DEPTH

The advanced tread width and tread depth helps provide long miles to removal in waste haul applications.

### HIGH WEAR-RESISTANT COMPOUND

The unique tread compound was specifically designed for waste haul applications.

### STONE PROTECTOR LEDGES

The stone protector ledges in the center groove help resist stone penetration and retention.

### DEEP TREAD DEPTH

The 24/32" tread depth helps provide extended tread wear in high-scrub applications.

### 10,000-LB. LOAD CAPACITY

A robust tire construction helps provide the load-carrying capacity for high-load steer axles.

**Competitive Replacements:** Falken GI388, Kumho KMA01, Double Coin RR716

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246342	173-016-005	315/80R22.5	L/20	160/157K	68 mph	(9.00) 9.00-9.75	130	10,000	9,090	43.03	12.6	19.96	13.8	482	24.0	28	10.7	165
					110 km/h		900	4,540	4,125	1,093	321	507	351	299	19.0	711	271	75.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM230 WB™

The RM230 WB™ is a steer all-position, heavy-duty, wide-base tire for mixed service applications.

### AGGRESSIVE ALL-POSITION TREAD DESIGN

The aggressive tread pattern has biting edges to handle rock and gravel terrain and helps provide all-position traction and handling for on- and off-road applications.

### CUT AND CHIP TREAD COMPOUND

The tread compound helps resist cuts and chips in mixed service applications.

### FOUR HEAVY-DUTY STEEL BELTS

Four heavy-duty steel belts promote durability in heavy-haul applications while also preserving the casing for retread.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

The curb bar with sidewall depth indicator helps protect the sidewall from scuffing damage and assist in indicating when a tire should be rotated to preserve the casing for retreading.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**M+S Rated**

**Competitive Replacements:** Falken GI378, Kumho KRA12, Double Coin RR905 & RLB980

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246208	173-012-003	385/65R22.5	L/20	160K	68 mph 110 km/h	(11.75) 11.75-12.25	130 900	9,920 4,500	---	42.36 1,076	15.3 389	19.61 498	---	489 304	22.5 18.0	46 1,168	12.2 311	175 79.7
246348	173-013-003	425/65R22.5	L/20	165K	68 mph 110 km/h	(12.25) 12.25-14.00	120 830	11,400 5,150	---	44.49 1,130	16.8 426	20.47 520	---	466 290	22.5 18.0	48 1,219	13.5 343	199 90.4

**This product cannot be used in dual applications.**

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM332 WB™

The RM332 WB™ is a heavy-duty, wide-base tire for steer axles in mixed service applications.

### DEEP TREAD DEPTH

The 23/32" tread depth helps provide extended tread wear in high-scrub applications.

### RIB-TYPE TREAD DESIGN

The tread pattern helps promote tread life and even wear in mixed service applications.

### CUT AND CHIP TREAD COMPOUND

The tread compound helps resist cuts and chips in mixed service applications.

### FOUR HEAVY-DUTY, FULL-WIDTH STEEL BELT CONSTRUCTION

Four heavy-duty, full-width steel belts help promote durability in heavy-haul while also preserving the casing for retread.

### STONE PROTECTOR LEDGES

The stone protector ledges in all four circumferential grooves help resist stone penetration and retention.

### CURB BAR ON SIDEWALLS

The curbing bar on both sidewalls helps protect the tire from curbing damage.

**Competitive Replacements:** Falken GI378, Kumho KRA12, Double Coin RR905 & RLB980

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246336	173-019-014	385/65R22.5	L/20	160K	68 mph	(11.75) 11.75-12.25	130	9,920	---	42.36	15.2	19.61	---	489	23.0	46	12.2	177
					110 km/h		900	4,500	---	1,076	387	498	---	304	18.1	1,168	311	80.3
246420	173-020-014	425/65R22.5	L/20	165K	68 mph	(12.25) 12.25-14.00	120	11,400	---	44.53	16.6	20.51	---	466	23.0	46	13.5	198
					110 km/h		830	5,150	---	1,131	422	521	---	289	18.1	1,168	343	90.0

**This product cannot be used in dual applications.**

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM300 HH™

The RM300 HH™ is an on/off-road drive tire designed to handle heavy hauling in mixed service applications.

### STONE PROTECTORS AND STONE PROTECTOR LEDGES

Stone protector ledges on all lugs and stone protectors on the bottom of the tread grooves help protect the casing from stone penetration.

### CURB BAR WITH SIDEWALL DEPTH INDICATOR

The curb bar with sidewall depth indicator helps protect the sidewall from scuffing damage and assists in indicating when a tire should be rotated to preserve the casing for retreading.

### CUT AND CHIP TREAD COMPOUND

The tread compound helps resist cuts and chips in mixed service applications.

### TREAD DEPTH

Rugged 29.5/32" tread depth helps provide traction and durability in mixed service applications.

### HIGH TENSILE STRENGTH FOUR-BELT PACKAGE

The high tensile strength four-belt package helps provide casing durability and retreadability.

**M+S Rated**

**Competitive Replacements:** Uniroyal HD2, Falken CI637, Kumho KMD41, Double Coin RLB600

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246332	173-010-005	11R22.5	H/16	146/143K	68 mph	(8.25) 7.50-8.25	120	6,610	6,005	42.13	11.3	19.61	12.5	492	29.5	26	9.0	126
					110 km/h		830	3,000	2,725	1,070	288	498	318	306	23.5	660	229	57.1
246415	173-038-005	11R24.5	H/16	149/146K	68 mph	(8.25) 7.50-8.25	120	7,160	6,610	44.09	11.2	20.59	12.5	470	29.5	26	9.0	133
					110 km/h		830	3,250	3,000	1,120	284	523	318	292	23.5	660	229	60.7

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM35I HD™

The RM35I HD™ is a versatile on/off road mixed service drive tire for logging, mining and construction.

### MIXED SERVICE TREAD COMPOUND

The mixed service tread compound helps resist cuts, chips and tears and provides long miles to removal.

### DEEP TREAD DEPTH

The 32/32" tread depth helps provide extended tread wear in high-scrub applications.

### STONE PROTECTORS

Stone protectors coupled with angled grooves help to prevent stone retention and aid in preserving the casing for retreading.

### OPTIMIZED SHOULDER DESIGN

Notches in shoulder lugs provide added traction while tie-bars help prevent heel-toe wear.

**M+S Rated**

**Competitive Replacements:** Uniroyal HD2, Falken CI637, Kumho KMD41, Double Coin RLB600

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246345	173-010-015	11R22.5	H/16	146/143K	68 mph	(8.25) 7.50-8.25	120	6,610	6,005	42.36	11.3	19.69	12.5	489	32.0	26	9.4	141
					110 km/h		830	3,000	2,725	1,076	287	500	318	304	25.5	660	240	64.0
246436	173-011-015	11R24.5	H/16	149/146K	68 mph	(8.25) 7.50-8.25	120	7,160	6,610	44.41	11.2	20.71	12.5	467	32.0	26	9.4	151
					110 km/h		830	3,250	3,000	1,128	285	526	318	290	25.5	660	240	68.5

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.

# URBAN | STEER/ALL POSITION



## RM170+™

The RM170+™ is a pick-up and delivery all-position tire.

### 87 MPH (N) SPEED RATING

The 225/70R19.5 and 245/70R19.5 LR G sizes offer the N speed rating.

### WIDE TREAD AND OPTIMIZED FOOTPRINT

The wide tread and optimized footprint help deliver long even treadwear.

### V-SHAPED TREAD GROOVES

The groove shapes help reduce stone retention.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.

**Competitive Replacements:** Uniroyal RS2, Falken G1388, Kumho KMA01, Double Coin RR706

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius inch mm	Dual Spcg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246168	173-025-024	225/70R19.5	F/12	125/123N	87 mph	(6.75) 6.00-6.75	95	3,640	3,415	32.05	9.0	14.92	10.0	647	15.0	28	7.6	62
					140 km/h		660	1,650	1,550	814	228	379	254	402	11.9	711	193	28.0
246449	173-026-024	225/70R19.5	G/14	128/126N	87 mph	(6.75) 6.00-6.75	110	3,970	3,750	32.05	9.0	14.92	10.0	647	15.0	28	7.6	62
					140 km/h		760	1,800	1,700	814	228	379	254	402	11.9	711	193	28.0
246451	173-027-024	245/70R19.5	G/14	133/131N	87 mph	(7.50) 6.75-7.50	110	4,540	4,300	33.11	9.9	15.35	11.0	626	16.0	26	8.4	71
					140 km/h		760	2,060	1,950	841	251	390	279	389	12.7	660	213	32.3
246450	173-028-024	245/70R19.5	H/16	136/134M	81 mph	(7.50) 6.75-7.50	120	4,940	4,675	33.11	9.9	15.35	11.0	626	16.0	26	8.4	71
					130 km/h		825	2,240	2,120	841	251	390	279	389	12.7	660	213	32.3
246452	173-029-024	265/70R19.5	G/14	137/134L	75 mph	(7.50) 7.50-8.25	110	5,070	4,675	34.37	10.3	15.87	11.6	603	17.5	30	8.6	81
					120 km/h		760	2,300	2,120	873	261	403	295	375	13.8	762	219	36.9
246453	173-030-024	10R22.5	G/14	141/139L	75 mph	(7.50) 6.75-8.25	115	5,675	5,355	40.31	10.1	18.82	11.4	514	18.0	24	7.9	100
					120 km/h		790	2,575	2,430	1,024	257	478	290	320	14.5	610	200	45.6

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.



## RM257™

The RM257™ is an open-shoulder pick-up and delivery drive tire designed to help perform in various weather conditions.

### TIGHTLY PACKED CENTER TREAD BLOCKS AND HIGH TENSILE STRENGTH BELT CONSTRUCTION

The tightly packed center tread blocks and high tensile strength belt construction help provide even wear, long miles to removal and casing retreadability.

### 87 MPH (N) SPEED RATING

The 225/70R19.5 and 245/70R19.5 LR G sizes offer the N speed rating.

### CURB BAR

The curb bar helps protect the sidewall from scuffing damage.

### 3D SIPING

3D corrugations on the sipes help to lock the tread blocks together to maintain stability for traction.

### STONE PROTECTORS

Stone protectors in the tread grooves help protect the casing from stone penetration and help resist stone retention.



**Competitive Replacements:** Uniroyal RS2, Falken G1388, Kumho KMA01, Double Coin RR706

\* Meets Three-Peak Mountain Snowflake (3PMSF) Traction Requirements

Material Number	Product Code	Tire Size	Load Range/ Ply Rating	Service Description	Speed Rating	(Measured) Approved Rim Widths	Inflation Pressure psi kPa	Single Max. Load lb./kg	Dual Max. Load lb./kg	Overall Diameter inch mm	Section Width inch mm	Static Loaded Radius in./mm	Dual Spg. inch mm	REVs miles km	Tread Depth 32nds mm	Buff Rad. inch mm	Buff Width inch mm	Ship Wt. lbs. kg
246278	173-025-009	225/70R19.5	F/12	125/123N	87 mph 140 km/h	(6.75) 6.00-6.75	95 660	3,640 1,650	3,415 1,550	32.24 819	9.1 230	15.00 381	10.0 254	643 400	18.0 14.3	18 457	7.2 184	65 29.3
246166	173-026-009	225/70R19.5	G/14	128/126N	87 mph 140 km/h	(6.75) 6.00-6.75	110 760	3,970 1,800	3,750 1,700	32.24 819	9.1 230	15.00 381	10.0 254	643 400	18.0 14.3	18 457	7.2 184	65 29.3
246446	173-027-009	245/70R19.5	G/14	133/131N	87 mph 140 km/h	(7.50) 6.75-7.50	110 760	4,540 2,060	4,300 1,950	33.35 847	10.0 254	15.47 393	11.0 279	622 386	19.0 15.2	22 559	8.0 203	72.0 32.5
246447	173-028-009	245/70R19.5	H/16	136/134M	81 mph 130 km/h	(7.50) 6.75-7.50	120 825	4,940 2,240	4,675 2,120	33.35 847	10.0 254	15.47 393	11.0 279	622 386	19.0 15.2	22 559	8.0 203	72.0 32.5
246324	173-031-009	255/70R22.5	H/16	140/137M	81 mph 130 km/h	(8.25) 6.75-8.25	120 830	5,510 2,500	5,070 2,300	37.28 947	10.2 260	17.36 441	11.6 295	556 346	26.0 20.7	28 711	8.3 210	99 45.2

Check [roadmastertrucktires.com](http://roadmastertrucktires.com) for updated data.





# ROADMASTER® TIRES

## Commercial Application Tire Selection Guide



<b>STEER</b>	RM832+ (EM) <sup>TM</sup>	RM230 WB <sup>TM</sup> RM830 (EM) <sup>TM</sup> RM230 HH <sup>TM</sup>	RM830 (EM) <sup>TM</sup> RM230 HH <sup>TM</sup>	RM832+ (EM) <sup>TM</sup> RM185 <sup>TM</sup>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM234 (EM) <sup>TM</sup>
<b>DRIVE</b>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup>
<b>TRAILER</b>	RM872 (EM) <sup>TM</sup> RM120 <sup>TM</sup>	RM185 <sup>TM</sup> RM170+ <sup>TM</sup> RM230 HH <sup>TM</sup> RM272 <sup>TM</sup>	RM230 HH <sup>TM</sup> RM185 <sup>TM</sup>	RM872 (EM) <sup>TM</sup> RM120 <sup>TM</sup> RM185 <sup>TM</sup>	RM230 HH <sup>TM</sup> RM185 <sup>TM</sup> RM234 (EM) <sup>TM</sup>



<b>STEER</b>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM234 (EM) <sup>TM</sup> RM230 HH <sup>TM</sup>	RM185 <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM832+ (EM) <sup>TM</sup>	RM332 WB <sup>TM</sup> RM230 WB <sup>TM</sup> RM830 (EM) <sup>TM</sup> RM230 HH <sup>TM</sup>	RM230 WH <sup>TM</sup>
<b>DRIVE</b>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM230 HH <sup>TM</sup> RM185 <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM185 <sup>TM</sup> RM230 HH <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM230 WH <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup>
<b>TRAILER</b>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM272 <sup>TM</sup>	RM872 (EM) <sup>TM</sup> RM120 <sup>TM</sup> RM234 (EM) <sup>TM</sup> RM185 <sup>TM</sup> RM230 HH <sup>TM</sup>	RM872 (EM) <sup>TM</sup> RM120 <sup>TM</sup>	<b>TAG FITMENT</b> RM185 <sup>TM</sup> RM170+ <sup>TM</sup> RM230 HH <sup>TM</sup>	



<b>STEER</b>	RM832+ (EM) <sup>TM</sup> RM170+ <sup>TM</sup> RM185 <sup>TM</sup> RM830 (EM) <sup>TM</sup>	RM234 (EM) <sup>TM</sup> RM185 <sup>TM</sup>	RM185 <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM332 WB <sup>TM</sup> RM230 WB <sup>TM</sup> RM230 HH <sup>TM</sup> RM830 (EM) <sup>TM</sup>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM185 <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM332 WB <sup>TM</sup> RM230 WB <sup>TM</sup> RM230 HH <sup>TM</sup>	RM185 <sup>TM</sup> RM230 HH <sup>TM</sup> RM234 (EM) <sup>TM</sup>
<b>DRIVE</b>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM185 <sup>TM</sup> RM830 (EM) <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>	RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM234 (EM) <sup>TM</sup>	RM254 <sup>TM</sup> RM258 WD <sup>TM</sup> RM300 HH <sup>TM</sup> RM351 HD <sup>TM</sup> RM230 HH <sup>TM</sup>	RM852 (EM) <sup>TM</sup> RM275 <sup>TM</sup> RM254 <sup>TM</sup> RM258 WD <sup>TM</sup>

## Load and Inflation Table for Radial Truck-Bus Tires

TIRE SIZE DESIGNATION	USAGE	TIRE LOAD LIMITS AT VARIOUS COLD INFLATION PRESSURES													
		kPa	480	520	550	590	620	660	690	720	760	790	830	860	900
		psi	70	75	80	85	90	95	100	105	110	115	120	125	130
245/70R17.5	DUAL	kg	1590	1700	1780	1880	1950	2050	2130	2200	2300	2370	2470	2575(J)	
		lbs.	3505	3750	3925	4145	4300	4520	4695	4850	5070	5225	5445	5675(J)	
	SINGLE	kg	1690	1800	1880	1990	2070	2170	2250	2330	2430	2510	2610	2725(J)	
		lbs.	3725	3970	4145	4385	4565	4785	4960	5135	5355	5535	5755	6005(J)	
215/75R17.5	DUAL	kg	1300	1390	1450	1540	1600	1680	1740	1800	1880	1940	2020	2060(H)	
		lbs.	2865	3065	3195	3395	3525	3705	3835	3970	4145	4275	4455	4540(H)	
	SINGLE	kg	1380	1470	1540	1630	1690	1780	1850	1910	1990	2060	2140	2180(H)	
		lbs.	3040	3240	3395	3595	3725	3925	4080	4210	4385	4540	4720	4805(H)	
235/75R17.5	DUAL	kg	1610	1720	1800	1900	1980	2080	2160	2230	2330	2410	2500	2575(J)	
		lbs.	3550	3790	3970	4190	4365	4585	4760	4915	5135	5315	5510	5675(J)	
	SINGLE	kg	1710	1820	1910	2020	2100	2200	2280	2360	2470	2550	2650	2725(J)	
		lbs.	3770	4010	4210	4455	4630	4850	5025	5205	5445	5620	5840	6005(J)	
225/70R19.5	DUAL	kg	1230	1300	1360	1410	1470	1550(F)	1580	1640	1700(G)				
		lbs.	2720	2860	3000	3115	3245	3415(F)	3490	3615	3750(G)				
	SINGLE	kg	1310	1380	1450	1500	1570	1650(F)	1690	1740	1800(G)				
		lbs.	2895	3040	3195	3315	3450	3640(F)	3715	3845	3970(G)				
245/70R19.5	DUAL	kg	1390	1460	1550	1590	1660	1750	1790	1850	1950(G)	2040	2120(H)		
		lbs.	3070	3220	3415	3515	3655	3860	3940	4075	4300(G)	4520	4675(H)		
	SINGLE	kg	1480	1550	1650	1700	1770	1850	1900	1970	2060(G)	2150	2240(H)		
		lbs.	3265	3425	3640	3740	3890	4080	4190	4335	4540(G)	4740	4940(H)		
265/70R19.5	DUAL	kg	1560	1640	1700	1780	1860	1950	2000	2000	2120(G)				
		lbs.	3430	3600	3750	3930	4095	4300	4405	4415	4675(G)				
	SINGLE	kg	1660	1740	1800	1900	1970	2060	2130	2200	2300(G)				
		lbs.	3650	3830	3970	4180	4355	4540	4685	4850	5070(G)				
285/70R19.5	DUAL	kg	1780	1870	1960	2070	2160	2270	2350	2430	2540	2620	2725	2800(H)	
		lbs.	3930	4125	4340	4555	4770	4980	5190	5395	5600	5805	6005	6175(H)	
	SINGLE	kg	1900	1990	2090	2210	2300	2410	2500	2590	2700	2790	2900	3000(H)	
		lbs.	4185	4390	4625	4855	5080	5305	5525	5745	5965	6180	6395	6610(H)	
10R22.5	DUAL	kg	1750	1830	1910	2000	2080	2160	2240	2300	2360	2430(G)			
		lbs.	3860	4045	4230	4410	4585	4760	4940	5075	5210	5355(G)			
	SINGLE	kg	1850	1940	2030	2120	2200	2280	2360	2430	2500	2575(G)			
		lbs.	4080	4280	4480	4675	4850	5025	5205	5360	5515	5675(G)			
11R22.5	DUAL	kg	1990	2080	2160	2250	2360	2460	2560	2650(G)	2680	2710	2725(H)		
		lbs.	4380	4580	4760	4950	5205	5415	5625	5840(G)	5895	5950	6005(H)		
	SINGLE	kg	2050	2160	2260	2370	2500	2600	2700	2800(G)	2870	2940	3000(H)		
		lbs.	4530	4770	4990	5220	5510	5730	5950	6175(G)	6320	6465	6610(H)		
12R22.5	DUAL	kg	2170	2260	2350	2440	2575	2630	2680	2725	2840	2960	3075(H)		
		lbs.	4780	4990	5190	5390	5675	5785	5895	6005	6265	6525	6780(H)		
	SINGLE	kg	2240	2360	2470	2580	2725	2820	2910	3000	3120	3240	3350(H)		
		lbs.	4940	5200	5450	5690	6005	6205	6405	6610	6870	7130	7390(H)		
255/70R22.5	DUAL	kg	1630	1710	1800	1860	1940	2000	2020	2090	2120	2230	2300(H)		
		lbs.	3585	3765	3970	4110	4275	4410	4455	4610	4675	4915	5070(H)		
	SINGLE	kg	1730	1820	1900	1980	2060	2120	2220	2300	2360	2450	2500(H)		
		lbs.	3815	4005	4190	4370	4550	4675	4895	5065	5205	5400	5510(H)		
275/70R22.5	DUAL	kg	1750	1870	1960	2070	2150	2260	2340	2430	2530	2610	2720	2800	2900(J)
		lbs.	3860	4125	4320	4565	4740	4980	5160	5355	5580	5755	5995	6175	6395(J)
	SINGLE	kg	1910	2030	2120	2250	2340	2460	2550	2640	2750	2840	2950	3040	3150(J)
		lbs.	4210	4475	4675	4960	5160	5425	5620	5820	6065	6260	6505	6700	6940(J)
295/75R22.5	DUAL	kg	1860	1950	2060	2130	2220	2300	2390	2470	2575(G)	2680	2820	3000(H)	
		lbs.	4095	4300	4540	4690	4885	5070	5260	5440	5675(G)	5920	6220	6610(H)	
	SINGLE	kg	2040	2140	2240	2340	2440	2500	2620	2710	2800(G)	2950	3100	3250(H)	
		lbs.	4500	4725	4940	5155	5370	5510	5780	5980	6175(G)	6500	6830	7160(H)	
315/80R22.5 RM830 EM	DUAL	kg	2310	2420	2575	2650	2750	2900	2970	3070	3150	3270	3450(J)	3590	3750(L)
		lbs.	5095	5345	5675	5840	6070	6395	6545	6770	6940	7210	7610(J)	7910	8270(L)
	SINGLE	kg	2540	2660	2800	2910	3030	3150	3260	3370	3450	3590	3750(J)	3940	4125(L)
		lbs.	5600	5875	6175	6415	6670	6940	7190	7440	7610	7920	8270(J)	8690	9090(L)
315/80R22.5 RM230 HH+	DUAL	kg	2310	2420	2575	2650	2750	2900	2970	3070	3150	3270	3450	3590	3750(L)
		lbs.	5095	5345	5675	5840	6070	6395	6545	6770	6940	7210	7610(J)	7910	8270(L)
	SINGLE	kg	2940	3090	3230	3370	3510	3650	3780	3910	4000	4160	4250	4410	4540(L)
		lbs.	6485	6800	7120	7430	7730	8050	8320	8610	8820	9180	9370	9730	10000(L)
315/80R22.5 RM230 WH	DUAL	kg	2680	2810	3000	3070	3190	3350	3440	3560	3650	3790	3875	4010	4125(L)
		lbs.	5900	6190	6610	6760	7030	7390	7570	7840	8050	8350	8540	8850	9090(L)
	SINGLE	kg	2940	3090	3250	3370	3510	3650	3780	3910	4000	4160	4250	4410	4540(L)
		lbs.	6485	6800	7160	7430	7730	8050	8320	8610	8820	9180	9370	9730	10000(L)
385/65R22.5	SINGLE	kg	2880	3060	3150	3350	3470	3650	3740	3850	4000	4100	4250	4380	4500(L)
		lbs.	6380	6720	6940	7350	7650	8050	8230	8510	8820	9050	9370	9650	9920(L)
425/65R22.5	SINGLE	kg	3430	3640	3750	3980	4130	4250	4440	4580	4750	4880	5150(L)		
		lbs.	7590	7990	8270	8740	9100	9370	9790	10100	10500	10700	11400(L)		
11R24.5	DUAL	kg	2110	2210	2300	2390	2500	2580	2660	2725(G)	2820	2910	3000(H)		
		lbs.	4660	4870	5070	5260	5510	5675	5840	6005(G)	6205	6405	6610(H)		
	SINGLE	kg	2190	2300	2410	2520	2650	2770	2890	3000(G)	3080	3160	3250(H)		
		lbs.	4820	5070	5310	5550	5840	6095	6350	6610(G)	6790	6970	7160(H)		
12R24.5	DUAL	kg	2300	2400	2500	2600	2650	2770	2890	3000	3080	3160	3250(H)		
		lbs.	5080	5300	5520	5730	5840	6095	6350	6610	6790	6970	7160(H)		
	SINGLE	kg	2380	2500	2630	2740	2900	3020	3140	3250	3350	3450	3550(H)		
		lbs.	5240	5520	5790	6040	6395	6650	6910	7160	7380	7600	7830(H)		
285/75R24.5	DUAL	kg	1870	1970	2060	2150	2240	2360	2410	2490	2575(G)	2660	2800(H)		
		lbs.	4135	4340	4540	4740	4930	5205	5310	5495	5675(G)	5860	6175(H)		
	SINGLE	kg	2060	2160	2240	2360	2460	2575	2650	2740	2800(G)	2920	3075(H)		
		lbs.	4545	4770	4940	5210	5450	5675	5835	6040	6175(G)	6440	6780(H)		



# STANDARD LIMITED WARRANTY

## REPLACEMENT ALL-STEEL RADIAL TRUCK TIRES

### ELIGIBILITY

This warranty applies to the original purchaser of a Roadmaster All-Steel Radial truck tire and is not transferable. Your tires were purchased on or after March 15, 2023. Eligible tires must be purchased new and used on the vehicle which they were originally installed. Additionally, they must be the size, load index, and speed rating equivalent or greater than that specified by the vehicle manufacturer. This warranty applies to the 48 contiguous continental United States, Alaska, Hawaii, District of Columbia and Canada. For warranty exclusions see "WHAT IS NOT COVERED".

### WHAT IS COVERED AND FOR HOW LONG

- Free Tire Replacement** – Roadmaster warrants to the original purchaser that if a Roadmaster All-Steel Radial Truck tire becomes unserviceable due to a covered warranty condition (excludes ride complaints) during the first 2/32" (1.6mm) of factory original tread wear or 12 months from date of purchase, whichever occurs first, the tire will be replaced with an equivalent new Roadmaster All-Steel Radial Truck tire without charge. You must pay for mounting, balancing, and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.
- Prorated Tire Replacement** – Roadmaster warrants to the original purchaser that if a Roadmaster All-Steel Radial Truck tire becomes unserviceable due to a covered warranty condition (excludes ride complaints) after the first 2/32" (1.6mm) of wear on original factory tread, the tire will be replaced with an equivalent new Roadmaster All-Steel Radial Truck tire on a prorated basis. A replacement charge (defined below) will be required in order to obtain a replacement tire.

### OTHER THAN FIRST QUALITY TRUCK TIRES

Roadmaster All-Steel Radial truck tires branded "BLEMISH" (non-uniform) have the same warranty as first quality tires except for ride complaints and the appearance or other conditions which caused the tires to be classified as other than first quality. Tires branded "NON-ADJ" (non-adjustable) are not covered by this Warranty.

### TREAD LIFE

When the tread becomes worn down to 2/32" (1.6 mm) anywhere on the tire (shown by tread wear indicators molded into the tread grooves) the tire is worn out and this warranty ends. Driving habits, driving conditions, tire and vehicle maintenance all play a part in the tread life of a tire and all differ with each purchaser. Safety information is located at [www.roadmastertires.com](http://www.roadmastertires.com) (and select: "Tire Safety"); and, from your dealer.

### REPLACEMENT CHARGE

The Replacement Charge will be determined by multiplying the dealer's current selling price by the percentage of original tread depth worn from the tire. You must pay for mounting, balancing and any other additional charges, such as taxes or the acceptance of a higher priced replacement tire.

### CASING ALLOWANCE

**LONG HAUL, REGIONAL & PICKUP & DELIVERY** casings, except 17.5 & 19.5 sizes, will be warranted for covered warranty conditions through the first retread for a period of six (6) years from the date of the casing DOT serial number or proof of purchase, if available. If retreaded by a Goodyear Authorized Retreader, except 17.5 & 19.5 sizes, will be warranted for covered warranty conditions for two (2) retreads for a period of six (6) years from the date of the casing DOT serial number or proof of purchase, if available. **OFF ROAD, MIXED SERVICE & WASTE HAUL** and 17.5 & 19.5 casings, will be warranted for covered warranty conditions through the first retread for a period of four (4) years from the date of the casing DOT serial number or proof of purchase, if available. If retreaded by a Goodyear Authorized Retreader, casings will be warranted for covered warranty conditions through two (2) retreads for a period of four (4) years from the date of the casing DOT serial number or proof of purchase, if available. Casing Values are based on the predetermined casing value at the time of adjustment. See your servicing Dealer for these values.

Radial truck tires branded "BLEMISH", "MAL-WEAR", "NON-UNIF" (non-uniform) or "NON-ADJ" (non-adjustable) are not eligible for a casing allowance.

### HOW TO OBTAIN AN ADJUSTMENT

Tire adjustments must be presented to your local Roadmaster dealer. You must present this booklet, proof of purchase and be the original owner when requesting a replacement for your tire. See "WHERE TO GO FOR WARRANTY REPLACEMENT".

### WHAT IS NOT COVERED

Adjustments will not be made for:

- Tires that become unserviceable due to:
  - Conditions resulting from road hazards, such as (A) impact damage, (B) cuts, (C) snags, or (D) punctures, or (E) vandalism.
  - Conditions such as, but not limited to, uneven, cupping, spotty, feathering tread wear resulting from (A) improper installation, (B) wheel misalignment, (C) tire/wheel assembly imbalance, (D) use of an improper rim, (E) improper mounting or dismounting or (F) misapplication, or (G) use of chains.
  - Conditions resulting from consumer damage, such as (A) improper tire and vehicle maintenance, (B) misuse, (C) abuse, (D) accident, fire or chemical corrosion, (E) underinflation, (F) overloading, (G) over deflection, (H) failure to follow recommended rotation practices.
- Ride complaints after the first 2/32" (1.6mm) of tread wear on the original factory tread.
- Ride complaints on tires branded "Blemish", "Mal-Wear", "Non-Uniform, or "Non-Adjustable".
- Use in any racing applications.

E. Ozone or weather checking on tires over (4) four years from date of manufacture or date of purchase. Proof of purchase is required. Without proof of purchase the manufacture date will be used to determine eligibility.

F. Tires stored Improperly OR

G. Tires that are:

- Worn unevenly and/or show a difference of 2/32" (1.6mm) between the grooves.
- Installed on any vehicle other than the vehicle on which they were first installed.
- Sold or adjusted outside the 48 contiguous continental United States, Alaska, Hawaii, District of Columbia and Canada.
- Acquired as used (tires purchased used or retreaded, equipped on a pre-owned vehicle, etc.).
- Altered in any manner (additional siping, buffing, stud pin holes, re-grooving, truing, etc.).
- Improperly repaired or with repairs not conforming to the U.S. Tire Manufacturer's Association standards.

### NO ROAD HAZARD COVERAGE

Many dealers sell or provide their own warranty coverage for road hazards and/or repairs. Roadmaster Tire does not provide this coverage. Check with your dealer to determine if Road Hazard/Repair coverage is available from them.

### WHEN DOES THE WARRANTY END?

**LONG HAUL, REGIONAL & PICKUP & DELIVERY** tires, except 17.5 & 19.5 sizes, have delivered the full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible or six (6) years from the new tires purchase date (whichever occurs first). Without proof of purchase, date of manufacture will be used to determine eligibility. Casings may continue to be warranted beyond the new tire coverage. Please refer to the "Casing Allowance" section for warranty details on casings.

**OFF ROAD, MIXED SERVICE & WASTE HAUL** and 17.5 & 19.5 Sizes, have delivered the full original tread life and the new tire coverage of this warranty ends when the treadwear indicators become visible or four (4) years from the new tires purchase date (whichever occurs first). Without proof of purchase, date of manufacture will be used to determine eligibility. Casings may continue to be warranted beyond the new tire coverage. Please refer to the "Casing Allowance" section for warranty details on casings.

### REPLACEMENT WARRANTY

If you receive a replacement tire under the terms of this Warranty, the replacement tire will be covered by the Warranty then currently given by Roadmaster for the replacement tire.

### WHERE TO GO FOR WARRANTY REPLACEMENT

You can obtain assistance in locating an independent Roadmaster dealer near you by visiting the dealer locator on our website at [www.roadmastertires.com](http://www.roadmastertires.com) or by calling 1-800-822-8686.

### CONDITIONS AND EXCLUSIONS

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the manufacturer. Nothing in this Warranty is intended to be a representation by Roadmaster that tire failure cannot occur.

**DISCLAIMER: THIS WARRANTY IS IN LIEU OF, AND COOPER TIRE HEREBY DISCLAIMS, ANY AND ALL OTHER WARRANTIES AND REPRESENTATIONS, EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND NO OTHER WARRANTY OR REPRESENTATION OF ANY KIND IS MADE BY COOPER TIRE OR SHALL BE IMPLIED BY LAW.**

**LIMITATION OF DAMAGES: IN NO EVENT AND UNDER NO CIRCUMSTANCE SHALL COOPER TIRE BE LIABLE TO THE BUYER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL, LOST PROFIT, LOSS OF BUSINESS, LOSS OF GOODWILL OR REPUTATION, PUNITIVE OR OTHER DAMAGE, COST (INCLUDING FOR REPLACEMENT TRANSPORTATION), EXPENSE OR LOSS OF ANY KIND. SOME STATES AND PROVINCES**

**DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU.**

### CONSUMER RIGHTS

This Warranty gives you specific legal rights, and you may also have other rights which vary from State to State or Province to Province.

### OWNER'S OBLIGATION

When making a claim, you must return the tire to be replaced to your Roadmaster dealer.

Proper vehicle and tire care is necessary to obtain the expected wear from a tire. It is your obligation to properly maintain your tires and the vehicle upon which they are mounted, including: (A) operating your tires at the inflation pressures recommended by the vehicle manufacturer, (B) keeping your tire/wheel assemblies in balance, (C) proper wheel alignment, and (D) rotation. You must check your tire's inflation pressure at least monthly and before long trips.

We recommend that you have your Roadmaster dealer inspect your tires any time you notice irregular or uneven tread wear and rotate them, if necessary. Also, they should be inspected by your dealer any time your vehicle is brought in for service.

For additional safety information please visit:

[www.ustires.org](http://www.ustires.org) [www.nhtsa.gov](http://www.nhtsa.gov) [www.safercar.gov](http://www.safercar.gov) [www.nsc.org](http://www.nsc.org)  
[www.tracanada.ca](http://www.tracanada.ca) [www.tc.gc.ca](http://www.tc.gc.ca)

## ROADMASTER TIRE

Visit our website at:  
[www.roadmastertires.com](http://www.roadmastertires.com)

For complete product and warranty details, please visit [roadmastertires.com](http://roadmastertires.com). ©2023 Goodyear Tire & Rubber Company. All Rights Reserved.

**ENGINEERED  
TO HANDLE  
EVERYTHING  
ALONG THE WAY.**



**ROADMASTER® TIRES**

Tire Ordering Infolink: 800-755-2772  
or Tire-HQ.com

Visit us at [www.RoadmasterTires.com](http://www.RoadmasterTires.com)