

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	495 /mph	124.70 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	26.00	75 mph	7.5-8.25 in	-	11 in	11 in
		308 /kms	56.60 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	21 mm	47 kph	-	-	284 mm	284 mm
11R22.5	H	494 /mph	123.50 lbs	6,610 lbs	120 psi	6,005 lbs	120 psi	-	26.00	75 mph	7.5-8.25 in	-	11 in	11 in
		307 /kms	56.00 kgs	2,998.20 kgs	827 kPa	2,723.80 kgs	827 kPa	-	21 mm	47 kph	-	-	287 mm	287 mm
11R24.5	G	472 /mph	133.60 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	26.00	75 mph	7.5-8.25 in	-	11 in	11 in
		293 /kms	60.60 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	21 mm	47 kph	-	-	282 mm	282 mm
11R24.5	H	472 /mph	132.40 lbs	7,160 lbs	120 psi	6,610 lbs	120 psi	-	26.00	75 mph	7.5-8.25 in	-	11 in	11 in
		293 /kms	60.10 kgs	3,247.70 kgs	827 kPa	2,998.20 kgs	827 kPa	-	21 mm	47 kph	-	-	282 mm	282 mm
285/75R24.5	G	495 /mph	127.00 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	26.00	75 mph	7.5-9.0 in	-	11 in	11 in
		308 /kms	57.60 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	21 mm	47 kph	-	-	274 mm	274 mm
295/75R22.5	G	508 /mph	120.00 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	26.00	75 mph	8.25-9.0 in	-	11 in	11 in
		316 /kms	54.40 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	21 mm	47 kph	-	-	282 mm	282 mm