



# RM230 HH™

## Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	H	498 /mph	122.60 lbs	6,610 lbs	120 psi	6,005 lbs	120 psi	-	22.50	68 mph	7.5-8.25 in	-	11 in	11 in
		309 /kms	55.60 kgs	2,998.20 kgs	827 kPa	2,723.80 kgs	827 kPa	-	18 mm	42 kph	-	-	287 mm	287 mm
11R24.5	H	475 /mph	131.30 lbs	7,160 lbs	120 psi	6,610 lbs	120 psi	-	22.50	68 mph	7.5-8.25 in	-	11 in	11 in
		295 /kms	59.60 kgs	3,247.70 kgs	827 kPa	2,998.20 kgs	827 kPa	-	18 mm	42 kph	-	-	279 mm	279 mm
12R22.5	H	484 /mph	140.50 lbs	7,390 lbs	120 psi	6,780 lbs	120 psi	-	22.50	68 mph	8.25-9.0 in	-	12 in	12 in
		301 /kms	63.70 kgs	3,352.00 kgs	827 kPa	3,075.40 kgs	827 kPa	-	18 mm	42 kph	-	-	305 mm	305 mm
12R24.5	H	461 /mph	150.20 lbs	7,830 lbs	120 psi	7,160 lbs	120 psi	-	22.50	68 mph	8.25-9.0 in	-	12 in	12 in
		286 /kms	68.10 kgs	3,551.60 kgs	827 kPa	3,247.70 kgs	827 kPa	-	18 mm	42 kph	-	-	302 mm	302 mm
275/70R22.5	J	542 /mph	114.80 lbs	6,940 lbs	130 psi	6,395 lbs	130 psi	-	22.00	68 mph	7.5-8.25 in	-	11 in	11 in
		337 /kms	52.10 kgs	3,147.90 kgs	896 kPa	2,900.70 kgs	896 kPa	-	17 mm	42 kph	-	-	279 mm	279 mm