



RM872 EM™

Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	506 /mph	109.30 lbs	6,175 lbs	105 psi	5,840 lbs	105 psi	-	12.00	75 mph	7.5-8.25 in	-	11 in	11 in
		314 /kms	49.60 kgs	2,800.90 kgs	723 kPa	2,649.00 kgs	723 kPa	-	10 mm	47 kph	-	-	282 mm	282 mm
11R24.5	G	483 /mph	117.40 lbs	6,610 lbs	105 psi	6,005 lbs	105 psi	-	12.00	75 mph	7.5-8.25 in	-	11 in	11 in
		300 /kms	53.30 kgs	2,998.20 kgs	723 kPa	2,723.80 kgs	723 kPa	-	10 mm	47 kph	-	-	284 mm	284 mm
285/75R24.5	G	506 /mph	110.90 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	12.00	75 mph	7.5-9.0 in	-	11 in	11 in
		314 /kms	50.30 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	10 mm	47 kph	-	-	274 mm	274 mm
295/75R22.5	G	522 /mph	103.90 lbs	6,175 lbs	110 psi	5,675 lbs	110 psi	-	12.00	75 mph	8.25-9.0 in	-	11 in	11 in
		324 /kms	47.10 kgs	2,800.90 kgs	758 kPa	2,574.10 kgs	758 kPa	-	10 mm	47 kph	-	-	287 mm	287 mm