

# RM832+EM™

## Tire Specifications Table

Tire Size	Load Range	Revs	Tire Weight	Single Max Load	Single Inflation Pressure	Dual Max Load	Dual Inflation Pressure	Static Loaded Radius	Tread Depth	Max Speed	Approved Rim Width in	Overall Diameter	Overall Width	Overall Width Loaded
11R22.5	G	497 /mph 309 /kms	121.20 lbs 55.00 kgs	6,175 lbs 2,800.90 kgs	105 psi 723 kPa	5,840 lbs 2,649.00 kgs	105 psi 723 kPa	-	18.00 14 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 282 mm	11 in 282 mm
11R22.5	H	497 /mph 309 /kms	121.20 lbs 55.00 kgs	6,610 lbs 2,998.20 kgs	120 psi 827 kPa	6,005 lbs 2,723.80 kgs	120 psi 827 kPa	-	18.00 14 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 282 mm	11 in 282 mm
11R24.5	G	474 /mph 295 /kms	129.90 lbs 58.90 kgs	6,610 lbs 2,998.20 kgs	105 psi 723 kPa	6,005 lbs 2,723.80 kgs	105 psi 723 kPa	-	18.00 14 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 282 mm	11 in 282 mm
11R24.5	H	474 /mph 295 /kms	129.90 lbs 58.90 kgs	7,160 lbs 3,247.70 kgs	120 psi 827 kPa	6,610 lbs 2,998.20 kgs	120 psi 827 kPa	-	18.00 14 mm	75 mph 47 kph	7.5-8.25 in	-	11 in 279 mm	11 in 279 mm
285/75R24.5	H	501 /mph 311 /kms	121.80 lbs 55.20 kgs	6,780 lbs 3,075.40 kgs	120 psi 827 kPa	6,175 lbs 2,800.90 kgs	120 psi 827 kPa	-	18.00 14 mm	75 mph 47 kph	7.5-9.0 in	-	11 in 277 mm	11 in 277 mm
295/75R22.5	G	516 /mph 321 /kms	114.80 lbs 52.10 kgs	6,175 lbs 2,800.90 kgs	110 psi 758 kPa	5,675 lbs 2,574.10 kgs	110 psi 758 kPa	-	18.00 14 mm	75 mph 47 kph	8.25-9.0 in	-	11 in 287 mm	11 in 287 mm
295/75R22.5	H	516 /mph 321 /kms	114.80 lbs 52.10 kgs	7,160 lbs 3,247.70 kgs	125 psi 861 kPa	6,610 lbs 2,998.20 kgs	125 psi 861 kPa	-	18.00 14 mm	75 mph 47 kph	8.25-9.0 in	-	11 in 287 mm	11 in 287 mm